



Dexter lifts have been manufactured in Finland for almost 40 years

Dexter trailer lifts are suitable for a wide range of applications. The small total weight and large reaches allow it to be used even in demanding places. Four independently adjustable support legs make it easier to level the lift, even on uneven and sloping surfaces. Continuous boom rotation and standard drive provide access to tight spaces. Thanks to the strong and sturdy frame, towing the lift is effortless and the long distances between work sites are not a problem.

All Dexter lifts are made of highstrength steel at our own factory in Nokia and are light but sturdy in relation to their lifting height. The products are designed for demanding operating conditions, with the goal of operational reliability and operational safety in particular. All crane service points are easily accessible and the joints are equipped with lubrication nipples. All components prone to damage are protected by metal guards.



19ZS / 25Z

Our top-of-the-line 19ZS and 25ZS lift models make working stable even in the upper air, thanks to a robust telescopic boom. The proportional boom steering standard on lifts is especially appreciated when working at heights. A petrol engine unit is also available as an option to operate the lift without mains power.



MAX WORKING HEIGHT 19ZS: 19,0 m 25Z: 25.0 m



MAX PLATFORM HEIGHT 19ZS: 17,0 m 25Z: 23,0 m



OUTREACH 19ZS: 6,5 m / 215 kg, 8,0 m / 120 kg 25Z: 8,5 m / 215 kg



WORKING WIDTH 19ZS: 4,6 m 25Z: 4,6 m



MAX LOAD 215 kg / 2 people



PLATFORM SIZE (I x w x h) 0,8 m x 1,25 m x 1,1 m



PLATFORM ROTATION +/-40°



BOOM ROTATION continuous



BOOM CONTROL proportional



MACHINE LENGTH 19ZS: 7,1 m 25Z: 8.55 m



MACHINE WIDTH 2.05 m



MACHINE HEIGHT 19ZS: 2,3 m 25Z: 2,4 m



MACHINE WEIGHT 19ZS: 2 200 kg 25Z: 3 000 kg



STANDARD POWER SOURCE 230V / 50 Hz / 1,9 kW electric motor



PETROL ENGINE optional



TRACTION DRIVE standard



GRADEABILITY 15 %



